# SAFETY DATA SHEET

## 1. Identification

Product number	1000023610
Product identifier	SC-AMR-006 REFILL MANGO
Revision date	03-06-2015
Company information	Vectair Systems Inc. PO Box 11068 Memphis, TN 38134 United States
Company phone	1-877-697-7276
Version #	03
Supersedes date	03-05-2015
Recommended use	Air Freshener
Recommended restrictions	None known.

2. Hazard(s) identification

Flammable aerosols	Category 1
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity, single exposure	Category 3 narcotic effects
Not classified.	
Not classified.	
	Serious eye damage/eye irritation Specific target organ toxicity, single exposure Not classified.

Signal word	Danger
Hazard statement	Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection.
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

## 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	40 - 60
Propane		74-98-6	20 - 40
Diethylene Glycol Monoethyl Ether		111-90-0	10 - 20
Other components below reportable let	vels		10 - 20

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Alcohol resistant foam. Water spray. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	

Precautions for safe handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Ту	(	,	/alue
Acetone (CAS 67-64-1)	PE	EL	2	400 mg/m3
			1	000 ppm
Propane (CAS 74-98-6)	PE	EL	1	800 mg/m3
			1	000 ppm
US. ACGIH Threshold Lir	nit Values			
Components	Ту	ре	V	/alue
Acetone (CAS 67-64-1)	ST	EL	7	50 ppm
	ΤV	VA	5	00 ppm
US. NIOSH: Pocket Guide	e to Chemical Hazard	ls		
Components	Ту	ре	V	/alue
Acetone (CAS 67-64-1)	Tν	VA	5	90 mg/m3
			2	50 ppm
Propane (CAS 74-98-6)	τv	VA	1	800 mg/m3
			1	000 ppm
US. Workplace Environm	nental Exposure Leve	I (WEEL) Guides		
Components	Ту	ре	V	/alue
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)	ΤV	VA		40 mg/m3
			2	5 ppm
ological limit values				
ACGIH Biological Exposu				
Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
* - For sampling details, pl	ease see the source d	ocument.		
propriate engineering ntrols	should be match or other engineer	ed to conditions. If ap ring controls to maint ave not been establis	oplicable, use pr ain airborne leve	hour) should be used. Ventilation rates ocess enclosures, local exhaust ventilation, els below recommended exposure limits. If airborne levels to an acceptable level. Provide
dividual protection measur Eye/face protection	=	protective equipme ses with side shields		
Hand protection	Wear appropriate	e chemical resistant o	gloves.	
Skin protection				
Other	Wear suitable pro	otective clothing.		
Respiratory protection	If permissible lev air-supplied resp		e NIOSH mecha	nical filter / organic vapor cartridge or an
Thermal hazards	Wear appropriate	e thermal protective of	clothing, when ne	ecessary.
neral hygiene nsiderations	after handling the		eating, drinking	sonal hygiene measures, such as washing J, and/or smoking. Routinely wash work nants.

## 9. Physical and chemical properties

Appearance

Physical state	Gas. Form
	Aerosol. Color
	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	132.89 °F (56.05 °C) estimated
Flash point	-156.0 °F (-104.4 °C) propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.6 % estimated
Flammability limit - upper (%)	14.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	258.6 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.682 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transp

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.	
Chemical stability	Material is stable under normal conditions.	
Possibility of hazardous reactions	Hazardous polymerization does not occur.	
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.	
Incompatible materials	Strong oxidizing agents.	
Hazardous decomposition products	No hazardous decomposition products are known.	

# 11. Toxicological information

Information on likely routes of ex	kposure	
Ingestion	Expected to be a low ingestion hazard.	
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Causes serious eye irritation.	
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.	

Information on toxicological effects

Acute toxicity	Narcotic effects.		
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal			
LD50	Guinea pig	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
	Rabbit	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
Inhalation			
LC50	Rat	55700 ppm, 3 Hours	
		132 mg/l, 3 Hours	
		50.1 mg/l	
Oral			
LD50	Rat	5800 mg/kg	
		2.2 ml/kg	
Diethylene Glycol Monoethyl Ether	(CAS 111-90-0)		
Acute			
Dermal			
LD50	Guinea pig	5900 mg/kg, Days	
	Rabbit	8500 mg/kg, 2 Hours	
		8476 mg/kg, 24 Hours	
		7714 mg/kg	
Oral			
LD50	Guinea pig	4970 mg/kg	
	Mouse	6031 mg/kg	
	Rabbit	5600 mg/kg	
	Rat	5600 mg/kg	
		5.4 ml/kg	
Propane (CAS 74-98-6)			
Acute			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
* Estimates for product may be	based on additional component data not shown.		
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritat	ion	
Serious eye damage/eye	Causes serious eye irritation.		
irritation			
Respiratory or skin sensitization			
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
OSHA Specifically Regulated Not listed.	Substances (29 CFR 1910.1001-1050)		
Reproductive toxicity This product is not expected to cause reproductive or developmental effects.		or developmental effects.	

Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful.

## 12. Ecological information

		uatic life with long lasting effects.		
•			Test Results	
Components		Species	Test Results	
Acetone (CAS 67-64-1) Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)				
Aquatic				
Fish	LC50	Bluegill (Lepomis macrochirus)	> 10000 mg/l, 96 hours	
* Estimates for product may I	be based on a	dditional component data not shown.		
Persistence and degradability	No data is	available on the degradability of this prod	luct.	
Bioaccumulative potential No data available.				
Partition coefficient n-octa	nol / water (lo	ng Kow)		
Acetone		-0.24		
Diethylene Glycol Monoethyl	Ether	-0.54		
Propane	No data av	2.36		
Mobility in soil	No data av			
Other adverse effects		dverse environmental effects (e.g. ozone endocrine disruption, global warming pote		
13. Disposal consideratio	ns			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Hazardous waste code The waste code should be assigned in discussion between the user, the producer and disposal company.				
US RCRA Hazardous Waste	e U List: Refe	erence		
Acetone (CAS 67-64-1)		U002		
Waste from residues / unused products	product res	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Since emp		aste handling site for recycling or disposal. e, follow label warnings even after container is	
14. Transport information	1			
DOT				
UN number	UN1950			
		lammable, (each not exceeding 1 L capac	city)	
Class	2.1			
Subsidiary risk	-			
Label(s)	2.1			
Packing group	Not applica			

Not applicable.

Packing group

	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306

Packaging on bulk None Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s) Packing	2.1
group Environmental	Not applicable.
hazards ERG Code	Yes
	10L
Special precautions for user	
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
	2.1
Subsidiary risk	2.1
Label(s) Packing	
group Environmental	Not applicable.
hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	
DOT	

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.		
TSCA Section 12(b) Export N Not regulated.	TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)		
CERCLA Hazardous Substance List (40 CFR 302.4)			
Acetone (CAS 67-64-1) SARA 304 Emergency release	Listed. e notification		
Not regulated. OSHA Specifically Regulated Not listed.	Substances (29 CFR 1910.1001-1050)		
Superfund Amendments and Rea	authorization Act of 1986 (SARA)		
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely hazard	ous substance		
Not listed.			
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Section Not regulated.	112 Hazardous Air Pollutants (HAPs) List		
5	112(r) Accidental Release Prevention (40 CFR 68.130)		
Safe Drinking Water Act (SDWA)	Not regulated.		
Drug Enforcement Admi Chemical Code Number	nistration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and		
Acetone (CAS 67-64-	1) 6532		

	dministration (DEA)  list  1.8	2 Exempt Chemical Mixtures (21 CFR 13	310(12(c))		
Acetone (CAS 67-	· · ·	35 %WV	510.12(0))		
	al Mixtures Code Number	00 /000			
Acetone (CAS 67-		6532			
US state regulations					
US. Massachusetts RTK -	Substance List				
Acetone (CAS 67-64-1	)				
Propane (CAS 74-98-6					
US. New Jersey Worker a	nd Community Right-to-Kno	ow Act			
Acetone (CAS 67-64-1					
Propane (CAS 74-98-6					
	and Community Right-to-K	now Law			
Acetone (CAS 67-64-1 Propane (CAS 74-98-6					
US. Rhode Island RTK	·)				
Acetone (CAS 67-64-1	)				
Propane (CAS 74-98-6	Propane (CAS 74-98-6)				
US. California Propositior	n 65				
		nt Act of 1986 (Proposition 65): This materi	al is not known to contain		
-	y listed as carcinogens or rep	roductive toxins.			
International Inventories					
Country(s) or region	Inventory name		On inventory (yes/no)*		
Australia	Australian Inventory of C	hemical Substances (AICS)	Yes		
Canada	Domestic Substances Lis		Yes		
Canada	Non-Domestic Substance	es List (NDSL)	No		
China	Inventory of Existing Che	mical Substances in China (IECSC)	Yes		
Europe	European Inventory of Ex Substances (EINECS)	kisting Commercial Chemical	Yes		
Europe	European List of Notified	Chemical Substances (ELINCS)	No		
Japan	Inventory of Existing and	New Chemical Substances (ENCS)	Yes		
Korea	Existing Chemicals List (	ECL)	No		
New Zealand	New Zealand Inventory		No		
Philippines	Philippine Inventory of Cl (PICCS)	nemicals and Chemical Substances	No		
United States & Puerto Ric	o Toxic Substances Contro	I Act (TSCA) Inventory	Yes		

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	12-05-2014
Revision date	03-06-2015
Version #	03
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	GHS: Classification