STANDARD LOCKER SERIES

GUARDIAN™

STANDARD FEATURES

- Knocked down construction for easy self assembly or save the labor and order them factory assembled.
- Classic III recessed handle designed to accept many styles of locks.
- 16 gauge solid door for clean, robust look.
- Available with Champagne Common Color bodies or in a single full color as an additional upgrade.
- Lightweight 24 gauge body parts.
- Sound dampening pan available to further reduce noise for a slamming door.



STRENGTH. FUNCTION. STYLE.

Storage for the places people learn, work, and gather.

EDUCATION WORKPLACE RECREATION

EXPLORE MORE.

AT A GLANCE

ABOUT PENCO

Penco's long history of providing storage solutions reflects its product expertise, innovation, and commitment to customer support.

MATERIALS

Steel: All Penco standard lockers are constructed using prime grade steel free from surface imperfection suitable for powder coating. Alternate material: Prime grade steel shall be fabricated using galvanneal steel and finished in the same manner. Forged steel coat hooks with balled ends and truss fin head bolts and hex nuts will be zinc coated and supplied for all lockers unless otherwise indicated.

STANDARD LOCKERS

- Multi-Point Latch Doors: ADA compliant; accepts combination locks, key locks, and padlocks.
- Hinges: 2 inch-high, 5-knuckle hinges.
- Solid Doors: Clean, smooth appearance.
- Ventilation: Slots in the door's return flange allow airflow.

ADDITIONAL OPTIONS

- Continuous Hinge: Available as an optional upgrade.
- 14-Gauge Door (Guardian Plus): A thicker door that adds durability for more demanding environments.
- Medallion Door: Features a sound pan welded to the inside of the door to help reduce noise when doors are slammed.
- SPL Defiant Door: Combines a 14-gauge door with a single-point latch, continuous hinge, and reinforcing pan.



1 Tier



2 Tier



3 Tier

FINISH

High quality powder coat paint finish applied in strict adherence to paint manufacturer's specifications to provide optimum appearance and performance. Finishes releasing VOCs are not acceptable. Standard coating thickness is 1 mil dry film thickness minimum. Powder Coat Plus option increases thickness to 2 mil minimum. Colors as selected from manufacturer's standard colors.

UL GREENGUARD
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818
GOLD





Defiant II Single Point Latch



Medallion (Option)



Guardian PLUS (Top and Bottom Doors)