

STANDARD LOCKER SERIES

Invincible II™

STANDARD FEATURES

- 14-gauge steel doors provide strength for demanding applications.
- Diamond perforations in doors and sides promote airflow and allow visual inspection.
- Available knocked down for self-assembly or factory assembled to save labor.
- Classic III recessed handles on 1-, 2-, and 3-tier lockers.
- Friction catch/door pulls on 4-, 5-, and 6-tier lockers.
- 16-gauge bodies with 18-gauge back.

STRENGTH. AIRFLOW. VISIBILITY.

Durable athletic storage with a clear view of locker contents.

EXPLORE MORE.

For more information or to place an order, contact your local District Sales Manager or visit www.pencoproducts.com.

INVINCIBLE II | STANDARD LOCKER SERIES

AT A GLANCE

ABOUT PENCO

Penco's long history of providing storage solutions reflects its product expertise, innovation, and commitment to customer support.

MATERIALS

Steel: All Penco standard lockers use prime grade steel, free from surface imperfections and suitable for powder coating.

Alternate Material: Prime grade galvanneal steel is fabricated and finished in the same manner. Forged steel coat hooks with balled ends, truss fin head bolts, and hex nuts are zinc coated and supplied for all lockers unless otherwise indicated.

STANDARD LOCKERS


- **Body:** 16-gauge, Back: 18-gauge, and Doors: 14-gauge.
- **Multi-Point Latch Doors:** ADA compliant; accepts combination locks, key locks, and padlocks.
- **Hinges:** 2-inch-high, 5-knuckle hinges.
- **Ventilation:** Diamond-perforated doors and sides promote airflow and visibility. Other ventilation options available.

ADDITIONAL OPTIONS

- **Continuous Hinge:** Available as an optional upgrade.
- **SPL Defiant Door:** Combines a 14-gauge door with a single-point latch, continuous hinge, and reinforcing pan.



Defiant II Single Point Latch



Classic III Recessed Handle



Friction Catch Door Pull



Cremone Multi-Point Turn Handle (Option)



1 Tier



2 Tier



3 Tier



4 Tier



5 Tier



6 Tier

FINISH

High quality powder coat paint finish applied in strict adherence to paint manufacturer's specifications to provide optimum appearance and performance. Finishes releasing VOCs are not acceptable. Standard coating thickness is 1 mil dry film thickness minimum. Powder Coat Plus option increases thickness to 2 mil minimum. Colors as selected from manufacturer's standard colors.

