STANDARD LOCKER SERIES

WELDED GEN2™

STANDARD FEATURES

- Factory-welded construction for strength in gyms and team locker rooms.
- Ships assembled from the factory to help reduce on-site assembly labor.
- Heavy-duty steel: 14-gauge doors, 16-gauge body and 18-gauge back.
- Diamond-shaped perforations in doors and sides provide airflow.
- Classic III recessed handles on 1-, 2- and 3-tier lockers.
- Friction catches with door pulls on 4-, 5- and 6-tier lockers.



FACTORY-WELDED. BUILT TO LAST.

Durable, visible storage for schools, workplaces, and recreation spaces.

EDUCATION WORKPLACE RECREATION

EXPLORE MORE.

For more information or to place an order, contact your local District Sales Manager or visit www.pencoproducts.com.

AT A GLANCE

ABOUT PENCO

Penco's long history of providing storage solutions reflects its product expertise, innovation, and commitment to customer support.

MATERIALS

Steel: All Penco standard lockers use prime grade steel, free from surface imperfections and suitable for powder coating.

Alternate Material: Prime grade steel shall be fabricated using galvanneal steel and finished in the same manner. Forged steel coat hooks with balled ends and truss fin head bolts and hex nuts will be zinc coated and supplied for all lockers unless otherwise indicated.

STANDARD LOCKERS

- **Multi-Point Latch Doors:** Accept combination locks, key locks, and padlocks. ADA-compliant configurations available.
- **Box Locker Doors:** Feature a friction catch and door pull; accept padlocks or built-in locks.
- **Hinges:** Full-length, 16-gauge continuous hinges.
- **Steel Construction:** Factory-welded, 16-gauge body with an 18-gauge back and 14-gauge doors.
- **Ventilation:** Diamond-shaped perforations in doors and sides allow airflow.

ADDITIONAL OPTIONS

- **SPL Defiant Door:** 14-gauge door with a single-point latch, continuous hinge and reinforcing pan.
- **Cremone Handle:** Multi-point turn handle option.



1 & 2 Tier | 3 & 4 Tier | 5 & 6 Tier

FINISH

High quality powder coat paint finish applied in strict adherence to paint manufacturer's specifications to provide optimum appearance and performance. Finishes releasing VOCs are not acceptable. Standard coating thickness is 1 mil dry film thickness minimum. Powder Coat Plus option increases thickness to 2 mil minimum. Colors as selected from manufacturer's standard colors.

GREENGUARD
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818
GOLD





Defiant II Single Point Latch



Classic III Recessed Handle



Friction Catch Door Pull



Cremone Multi-Point Turn Handle